



EC-TYPE EXAMINATION CERTIFICATE

Equipment or Protective System Intended for use
in Potentially Explosive Atmospheres
Directive 94/9/EC

EC-Type Examination Certificate Number : **BAS99ATEX2227**

Equipment or Protective System: **EVOLUTION JUNIOR FLOODLIGHT IIB**

Manufacturer: **CHALMIT LIGHTING LIMITED**

Address: **Glasgow, Scotland, G52 4BL**

This equipment or protective system and any acceptable variation thereto is specified in the schedule to this certificate and the documents therein referred to.

The Electrical Equipment Certification Service, notified body number 600 in accordance with Article 9 of the Council Directive 94/9/EC of 23 March 1994, certifies that this equipment or protective system has been found to comply with the Essential Health and Safety Requirements relating to the design and construction of equipment and protective systems intended for use in potentially explosive atmospheres given in Annex II to the Directive.

The examination and test results are recorded in confidential Report N°

BASEEFA Certification Report 99(C)0311 dated 22 December 1999

Compliance with the Essential Health and Safety Requirements has been assured by compliance with:

EN 50014: 1997 + Amd 1 & 2

EN 50018: 1994

EN 50019: 1994

except in respect of those requirements listed at item 18 of the Schedule.

If the sign "X" is placed after the certificate number, it indicates that the equipment or protective system is subject to special conditions for safe use specified in the schedule to this certificate.

This EC-TYPE EXAMINATION CERTIFICATE relates only to the design and construction of the specified equipment or protective system. If applicable, further requirements of this Directive apply to the manufacture and supply of this equipment or protective system.

The marking of the equipment or protective system shall include the following:-



II 2 G

EEx de IIB T* (T_{amb} = -50°C to *°C) *See Schedule


This certificate may only be reproduced in its entirety and without any change, schedule included.

File No: EECS 0068/01/014

This certificate is granted subject to the general conditions of the Electrical Equipment Certification Service. It does not necessarily indicate that the apparatus may be used in particular industries or circumstances.



Electrical Equipment Certification Service
Health and Safety Executive
Harpur Hill, Buxton, Derbyshire. SK17 9JN. United Kingdom
Tel: 01298 28000 Fax: 01298 28244



I M CLEARE

**I M CLEARE
DIRECTOR
11 January 2000**



13

Schedule

14

EC-TYPE EXAMINATION CERTIFICATE N° BAS99ATEX2227

15

Description of Equipment or Protective System

The Evolution Junior Floodlight IIB comprises a sand cast or die cast aluminium rectangular lamp housing with an integral increased safety terminal enclosure at one end and a threaded cover at the other. The luminaire may be fitted with either a 70W SON/T, or a 70W HQI-E lamp. A potted lampholder, containing an ignitor, passes through the wall of the increased safety terminal enclosure into the lamp housing. Leads are passed from the increased safety terminal enclosure into the lampholder, and the lamp housing, via Bartec line bushings Type 07-9101-H02D and Type 07-9101-H03D respectively. The line bushings are to Certificate PTB 97ATEX1047U, coded EEx d IIC, and marked Ex II 2 G. The lamp housing also contains a ballast located behind the lamp reflector, and a capacitor located behind the threaded cover.

Cemented into a recess in the top of the lamp housing is a glass window, which is retained by a rectangular frame secured by 8 M8 x 15 mm socket head cap screws of grade A2-70 stainless steel. The heads of the screws are potted to prevent removal.

The enclosure may be manufactured from the alternative materials of brass or gunmetal, and various light shields and a window cover guard may be fitted.

Internal and external earth facilities are provided.

An enclosure without the threaded cover, the ballast, the capacitor, or the Bartec bushing from the increased safety terminal enclosure into the lamp housing, is provided for the luminaires when fitted with double ended tungsten halogen lamps of 150, 200, 250 or 300 watts. A secondary glass may be clamped in contact with the cover glass for these fittings.

The installer shall use an appropriate method to ensure a minimum ingress protection of IP54 or higher IP rating to match that on the label at each entry, choosing cable entry devices in accordance with a recognised Code of Practice/Installation Instructions.

The temperature classifications and maximum ambient temperatures for each lamp type are indicated in the table below.

Lamp	Maximum Wattage	Secondary Glass Fitted	Temperature Classification	Maximum Ambient Temperature (°C)
Tungsten Halogen	300	Yes	T2	40
		No	T2	50
	250	Yes	T2	40
		No	T3	20
	200	Yes	T2	50
		No	T3	40
		Yes	T3	25
	150	Yes	T3	55
		No	T3	55



13

Schedule

14

EC-TYPE EXAMINATION CERTIFICATE N° BAS99ATEX2227

Lamp	Maximum Wattage	Secondary Glass Fitted	Temperature Classification	Maximum Ambient Temperature (°C)
SON/T	70	-	T3	55
		-	T4	40
HQI-E	70	-	T3	55
		-	T4	40

16

Report No.

BASEEFA Certification Report No. 99(C)0311

17

Special Conditions For Safe Use

None

18

Essential Health and Safety Requirements

Essential Health and Safety Requirements not covered by Standards listed at (9)		
Clause	Subject	Compliance
1.0.2	Analysis of possible operating faults	BASEEFA Report No. 99(C)0311
1.0.3	Special checking and maintenance conditions	No special requirements
1.0.6	Instructions	BASEEFA Report No. 99(C)0311
1.2.2	Components for incorporation or replacement	See Manufacturer's Instructions
1.2.4	Dust deposits	Certification for gas atmospheres only
1.2.5	Additional means of protection	Not applicable
1.2.7	Protection against other hazards	BASEEFA Report No. 99(C)0311
1.3.5	Hazards arising from pressure compensation	Not applicable
1.5.	General requirements for safety devices	Not applicable
1.6.1	Manual override	Not applicable
1.6.2	Emergency shutdown	Not applicable
1.6.3	Hazards arising from power failure	Not applicable
1.6.5	Placing of warning devices as parts of equipment	Not applicable
2.0.	Category M	Not applicable
2.1.	Category 1	Not applicable
2.2.1	Category 2G	BASEEFA Report No. 99(C)0311
2.2.2	Category 2D	Not applicable
2.3.	Category 3	Not applicable
3.	Requirements for protective systems	Not applicable



13

Schedule

14

EC-TYPE EXAMINATION CERTIFICATE N° BAS99ATEX2227

19

DRAWINGS

Number	Sheet	Issue	Date	Description
D1902	1	-	10.3.99	General Assembly - Evolution Junior (IIB)
D1902	2	-	10.3.99	General Assembly - Evolution Junior (IIB)
D1902	3	-	10.3.99	General Assembly - Evolution Junior (IIB)
D1902	4	-	10.3.99	General Assembly - Evolution Junior (IIB)

This certificate may only be reproduced in its entirety and without any change, schedule included.

BASEEFA List Keywords
2FLODLUM



1 **SUPPLEMENTARY EC-TYPE EXAMINATION CERTIFICATE**

2 **Equipment or Protective System Intended for use**
3 **in Potentially explosive atmospheres**
4 **Directive 94/9/EC**

5 Supplementary EC-Type Examination Certificate Number: **BAS99ATEX2227/1**

6 Equipment or Protective System: **EVOLUTION JUNIOR FLOODLIGHT IIB**

7 Manufacturer: **CHALMIT LIGHTING LIMITED**

8 Address: **Glasgow, Scotland, G52 4BL**

9 This supplementary certificate extends EC-Type Examination Certificate No. BAS99ATEX2227 to
10 apply to equipment or protective systems designed and constructed in accordance with the
11 specification set out in the Schedule of the said Certificate but having any variations specified in the
12 Schedule attached to this certificate and the documents therein referred to.

13 This Supplementary Certificate shall be held with the original Certificate.


14 This certificate may only be reproduced in its entirety and without any change, schedule included.

15 File No: EECS 0068/01/014

16 This certificate is granted subject to the general conditions of the Electrical
17 Equipment Certification Service. It does not necessarily indicate that the apparatus
18 may be used in particular industries or circumstances.



19 **Electrical Equipment Certification Service**
20 **Health and Safety Executive**
21 **Harpur Hill, Buxton, Derbyshire, SK17 9JN, United Kingdom**
22 **Tel: +44(0)1298 28000 Fax: +44(0)1298 28244**
23 **internet: www.baseefa.com e-mail: baseefa.info.eecs@hsl.gov.uk**



24 **I M CLEARE**
25 **DIRECTOR**
26 **7 June 2001**



13 **Schedule**

14 **SUPPLEMENTARY EC-TYPE EXAMINATION CERTIFICATE N° BAS99ATEX2227/1**

Description of the Variation to the Equipment or Protective System

VARIATION 1.1

To permit the following changes to the ignitor housing.

- a) Replacement of the line bushing with potted cables type H07G-K. (Tungsten halogen lamps only.)
- b) Addition of an external web.
- c) Replacement of the tapped ring with screw bosses for the lampholder. (Tungsten halogen lamps only.)
- d) Increase in the length of the flamepath.

16 **Report No.**

BASEEFA Certification Report No. 01(CI)0288 dated 31 May 2001

17 **Special Conditions For Safe Use**

See original certificate.

18 **Essential Health and Safety Requirements**

See original certificate.

19 **DRAWINGS**

Number	Issue	Date	Description
D1902 Sheets 1-4 inc.	1	21.05.01	General Assembly - Evolution Junior (IIB)

This certificate may only be reproduced in its entirety and without any change, schedule included.



1 **SUPPLEMENTARY EC - TYPE EXAMINATION CERTIFICATE**

2 **Equipment or Protective System Intended for use in Potentially Explosive Atmospheres
Directive 94/9/EC**

3 Supplementary EC - Type Examination Certificate **BAS99ATEX2227/2**
Number :

4 Equipment or protective system: **Evolution Junior Floodlight IIB**

5 Manufacturer : **Chalmit Lighting**

6 Address : **Glasgow, G52 4BL**

7 This supplementary certificate extends EC - Type Examination Certificate No. **BAS99ATEX2227** to apply to equipment or protective systems designed and constructed in accordance with the specification set out in the Schedule of the said certificate but having any variations specified in the Schedule attached to this certificate and the documents therein referred to.

This Supplementary Certificate shall be held with the original Certificate

The original certificate was issued by The Electrical Equipment Certification Service, Notified Body Number 0600, which retains responsibility for its original documentation. Baseefa (2001) Ltd., Notified Body Number 1180, is responsible only for the additional work relating to this supplementary certificate and any other supplementary certificate it has issued.

This certificate may only be reproduced in its entirety, without any change, Schedule included.

Baseefa Customer Reference No. **0068**

Project File No. **04/0858**

This certificate is granted subject to the general terms and conditions of Baseefa (2001) Ltd. It does not necessarily indicate that the equipment may be used in particular industries or circumstances.

Baseefa

Rockhead Business Park, Staden Lane,
Buxton, Derbyshire SK17 9RZ

Telephone +44 (0) 1298 766600 Fax +44 (0) 1298 766601

e-mail info@baseefa.com web site www.baseefa.com

Baseefa is a trading name of Baseefa (2001) Ltd
Registered in England No. 4305578 at the above address.

A handwritten signature in black ink, appearing to read "M. Powney".
PPR S SINCLAIR
DIRECTOR
On behalf of
Baseefa (2001) Ltd.



13

Schedule

14

Certificate Number BAS99ATEX2227/2

15 **Description of the variation to the Equipment or Protective System**

Variation 2.1

To permit the use of an alternative 2 core line bushing to Baseefa04ATEX0317U.

16 **Report Number**

None

17 **Special Conditions for Safe Use**

None

18 **Essential Health and Safety Requirements**

See original certificate

19 **Drawings and Documents**

Number	Sheet	Issue	Date	Description
D1902	1	03	29.11.04	General Assembly - Evolution Junior IIB
D1902	2	03	29.11.04	General Assembly - Evolution Junior IIB
D1902	3	03	29.11.04	General Assembly - Evolution Junior IIB
D1902	4	03	29.11.04	General Assembly - Evolution Junior IIB