



防 爆 电 气 设 备
Electrical Apparatus for Explosive Atmospheres

防 爆 合 格 证

CERTIFICATE OF CONFORMITY

编 号: CNEx07.1168
Serial No.

制造单位
Manufacturer

CHALMIT LIGHTING LTD
388 Hillington Road, Glasgow, G52 4BL

样品名称
Name of Product

Luminaire Protecta III

型号规格
Type of Product

PRGE/****/** (GRP/PC Enclosure)

防爆标志
Marking

Ex eqm IIT4 (Tamb: -20°C to +55°C)

产品标准
Standard

总装图号
Drawing No.

D2567, D2568, D2570, D2636, D2635, D6010

经对上述产品图样及技术文件的审查和样品的检验, 确认符合下列标准:

The drawings, technical documents and the samples are verified and certified according to standard(s) for safety as below:

- GB 3836.1-2000 Electrical apparatus for explosive gas atmospheres Part 1: General requirements
- GB 3836.3-2000 Electrical apparatus for explosive gas atmospheres Part 3: Increased safety "e"
- GB 3836.7-2004 Electrical apparatus for explosive gas atmospheres Part 7: Powder filling "q"
- GB 3836.9-2006 Electrical apparatus for explosive gas atmospheres Part 9: Encapsulation "m"

记 事
Note


See the appendix

本证有效期

Valid Date

From July 25, 2007 to July 24, 2012

中心主任
Director



国家防爆电气产品质量监督检验中心

CHINA NATIONAL QUALITY SUPERVISION AND TEST
CENTRE FOR EXPLOSION PROTECTED ELECTRICAL PRODUCTS

颁发日期
Issue Date

July 25, 2007

年 月 日

注: 本证仅对符合送检样品的产品有效, 证书持有者有责任保证产品符合标准规定。

Note: This certificate is only valid for the products which identify with the sample(s) tested and verified. Holder(s) of this certificate have the responsibility to ensure the products complying with relevant standard(s).

地址: 河南省南阳市仲景北路20号 邮政编码: 473008 电话: 0377-63258564, 63258555 传真: 0377-63208175, 63225471
Address: Nanyang, Henan, P.R. China post code: 473008 Tel: 0377-63258564, 63258555 Fax: 0377-63208175, 63225471
E-mail: cqst@cn-ex.com Http://www.china-ex.com



防 爆 电 气 设 备
Electrical Apparatus for Explosive Atmospheres

防爆(检验)合格证附页

APPENDIX TO CERTIFICATE OF CONFORMITY

证书编号:
Serial No.

CNEx07.1168

page 1 of 2

1. The luminaires may be marked depending on lamp type as follows:

Body Material	Lamp Type	Model	Lamps	Ambient Temperature range	T Class	Voltage (V a.c.)
GRP	Mono-pin	Non-emergency	2 × 18W	-20℃ to +55℃	T4	110-130V 50/60Hz, 200-254V 50/60Hz
			1 × 36W			
			2 × 36W			
		Emergency	2 × 18W			
			2 × 36W			
	Bi-pin	Non-emergency	2 × 18W	-20℃ to +55℃		
			1 × 36W			
			2 × 36W			
Emergency		2 × 18W				
		2 × 36W				
Stainless Steel	Mono-pin	Non-emergency	2 × 18W	-20℃ to +55℃		
			1 × 36W			
			2 × 36W			
		Emergency	2 × 18W	-20℃ to +45℃		
			2 × 36W			
	Bi-pin	Non-emergency	2 × 18W	-20℃ to +55℃		
			1 × 36W			
			2 × 36W			
Emergency		2 × 18W	-20℃ to +45℃			
		2 × 36W				

中心主任
Director



国家防爆电气产品质量监督检验中心
CHINA NATIONAL QUALITY SUPERVISION AND TEST
CENTRE FOR EXPLOSION PROTECTED ELECTRICAL PRODUCTS

颁发日期
Issue Date

July 25, 2007



地址: 河南省南阳市仲景北路20号 邮政编码: 473008 电话: 0377-63258564, 63258555 传真: 0377-63208175, 63225471
Address: Nanyang, Henan, P. R. China Post code: 473008 Tel: 0377-63258564, 63258555 Fax: 0377-63208175, 63225471
E-mail: cqst@cn-ex.com Http://www.china-ex.com



防 爆 电 气 设 备
Electrical Apparatus for Explosive Atmospheres

防爆(检验)合格证附页

APPENDIX TO CERTIFICATE OF CONFORMITY

证书编号:
Serial No.

CNEx07.1168

page 2 of 2

2. Alternatively Bi-Pin types fitted with a closed cell silicone gasket may be used within a lower ambient temperature of -40°C.
3. Non-emergency types are suitable for V d.c. of 110-156 and 220-300Vd.c.
4. GRP models are identified by the catalogue code PRGE/**/, and the stainless steel models are identified by PRSE/**/. The code further defines the number and wattage of lamps, bi-pin or mono pin, emergency, voltage etc.

中心主任
Director



国家防爆电气产品质量监督检验中心

CHINA NATIONAL QUALITY SUPERVISION AND TEST
CENTRE FOR EXPLOSION PROTECTED ELECTRICAL PRODUCTS

颁发日期
Issue Date

July 25, 2007

年 月 日

地址: 河南省南阳市仲景北路20号 邮政编码: 473008 电话: 0377-63258564, 63258555 传真: 0377-63208175, 63225471
Address: Nanyang, Henan, P. R. China Post code: 473008 Tel: 0377-63258564, 63258555 Fax: 0377-63208175, 63225471
E-mail: cqst@cn-ex.com Http://www.china-ex.com