




Bulkhead Light Fitting Series 6388

- Explosion protection to
 - CENELEC
 - IEC
- Can be used in Zone 1 and Zone 2
- Suitable for incandescent lamps up to 100 W
- Through-wiring possible

STAHL

The innovative layout of lamp-holder and terminals enables series 6388 light fittings to be mounted without heat-resistant cables and without additional junction box.

Selection table

Version	Description		Ordering code	Weight [kg]
	Lamps	Lampholder		
 6388 Ceiling fitting	Bulkhead light fitting	up to 100 W	E 27	6388/1 3,8 kg

Note: The light fittings are supplied without lamps, see accessories.

Technical data									
Explosion protection Lamps	EEx e T* * Temperature class 25/40 W T3 60 W T2 100 W T1								
Test certificate	L.C.I.E. 96.D.6091 other certificates: FTZU (Czech Republic), SEV (Switzerland), BKI (Hungary), VNIIEF (Russia), SZS (Yugoslavia)								
Material Housing Wire guard Glass	Light cast alloy Steel wire, galvanized Pressed glass, resistant to temperature changes								
Lamps	Incandescent lamps, E 27 lampholder, for 25 W, 40 W, 60 W, 100 W								
Rated voltage	250 V								
Efficiency of fitting	50%								
Luminous flux	<table border="1"> <tr> <th>25 W</th> <th>40 W</th> <th>60 W</th> <th>100 W</th> </tr> <tr> <td>200 lm</td> <td>325 lm</td> <td>575 lm</td> <td>1160 lm</td> </tr> </table>	25 W	40 W	60 W	100 W	200 lm	325 lm	575 lm	1160 lm
25 W	40 W	60 W	100 W						
200 lm	325 lm	575 lm	1160 lm						
Luminous intensity distribution	<p style="text-align: center;">Z3014P measuring level</p>								
Degree of protection	IP 54								
Ambient temperature	- 30 °C ... + 40 °C								
Cover fixing	M6, Hexagonal screw								
Connections	Terminals L1 + N for 2 x 4 mm ² flexible/solid PE for 2 x 6 mm ² flexible/solid								
Cable entry	1 x M25 x 1,5 cable gland 1 x M25 x 1,5 plug								



Accessories and spare parts

Designation	Illustration	Description	Ordering code	Weight [kg]
Incandescent lamp		230 V 25 W	512 658 0	0,032
		40 W	512 659 0	0,032
		60 W	512 660 0	0,032
		100 W	461 620 0	0,032
Mounting brackets		1 set	461 593 0	0,200

